



MILBOOK F10

10.1 inch Rugged Tablet

Performance

- Intel Core i5-1235U/i7-1255U processor
- Windows 11 OS and 8GB RAM+128GB storage
- 10.1 inch IPS Full HD screen with 10-point capacitive touch

Communication

- WIFI 6
- High speed 4G LTE
- BT 5.1 fast transmission

Features

- Choose 1 from 4 modules (2D scan engine, RJ45 Gigabit Ethernet, DB9 and USB2.0)
- Support GPS, BDS and GLONASS
- Equipped with multiple accessories, like docking charger, hand-strap, vehicle mount, car charge, carry handle

Reliability

- IP65 Waterproof and Dustproof, Anti-Static
- Vibration & 1.22m drop resistant
- MIL-STD-810G certified

Product Six Views



Specification Parameter

Basic parameters	
Dimension	289.9 x 196.7 x 27.4mm
Weight	device unit 1140g
Device Color	black
LCD	10.1 inch IPS 16:10, 1200×1920
Touch Panel	10 points Capacitive, G+G, Corning Gorilla Glass
Camera	Front 2.0MP, Rear 8.0MP
I/O	USB 3.0 Type-A x 1, USB Type-C x 1, SIM Card x 1, SD Card x 1, HDMI 1.4a x 1, 12pins Pogo Pin x 1, Φ3.5mm standard earphone jack x 1, Φ5.5mm DC jack x 1
Power	AC100V ~ 240V, output DC 19V/3.42A/65W
NFC	Built-in NXP100
Fingerprint	SPI fingerprint (windows hellow boot login)
Battery	
Capacity	7.4V/700mAh
Type	Built-in Li-polymer battery
Endurance	30 mins (50% volume sounds, 200 lumens brightness, 1080P HD video display by default)
Battery	
Capacity	7.4V/5000mAh
Type	Removable Li-polymer battery
Endurance	6hrs (50% volume sounds, 200 lumens brightness, 1080P HD video display by default)

Accessories



Docking Charger



Hand-strap



Vehicle Mount



Car Charge



Removable Battery



Carry handle

Application Range

Various modules and accessories can be selected to meet customers' application in various industries.



Performance parameter	
CPU	Intel Core i5-1235U/i7-1255U
OS	Windows 11
RAM	8GB, Optional 16GB, Up to 64GB
Storage	128GB, Optional 256GB, Up to 512GB
Network connections	
WIFI	Wi-Fi 6 802.11a,b,d,e,g,h,i,k,n,r,u,v,w,ac,ax
Bluetooth	BT5.1
4G	LTE FDD: B1/B3/B7/B8/B20/B28A WCDMA: B1/B8 GSM: B3/B8
GNSS	Built-in GPS, glonass
Reliability	
Operate Temperature	-20 °C ~ 60 °C
Store Temperature	-30 °C ~ 70 °C
Humidity	95% Non-Condensing
Rugged Feature	IP65 certified, MIL-STD-810G certified
Drop Height	1.22m drop
Electrostatic Discharge	± 8kV contact discharge, ± 15kV air discharge
Extension modules (1 out of 4)	
Ethernet interface	RJ45 (10/100M) x 1, Support customized (10/100/1000M)
Serial port	DB9 (RS232) x 1
USB2.0	USB 2.0 x 1
2D	Honeywell N3680, Optical resolution: 5mil/scan speed: 50 times/s

Dystrybucja i serwis:
AP-FLYER Sp. z o. o., ul. Żegańska 2d, 04-713
Warszawa Tel: +48 22 613 0487, Fax: +48 22 613 0612
www.milbook.pl info@milbook.pl